

| APPROVED METER SOCKETS 120/240V CUSTOMERS WITH EMBEDDED GENERATION |     |                                |                            |                        |
|--|-----|--------------------------------|----------------------------|------------------------|
| ТҮРЕ   |     | MANUFACTURER                   |                            |                        |
|  |     | THOMAS AND BETTS MICROELECTRIC | EATON<br>CUTLER-<br>HAMMER | HYDEL<br>MURRAY JENSEN |
| 1 - POSITION   |     |                                |                            |                        |
| 200A MAIN, 2-POS<br>100 AMP/POS                                    | U/G | BEC2-VA                        | 2KN1                       | SD220PW                |
|  | O/H | BE2-V                          | 2KN1                       | SD220PW                |
| 200A MAIN, 2-POS<br>200 AMP/POS                                    | U/G | BDC2-V                         | 2K2                        | H22R                   |
|  | О/Н | BD2-V                          | 2K2                        | H22R                   |
| 400A MAIN, 2-POS<br>200 AMP/POS                                    | U/G | BS42-V                         | 2K4                        | HC42R                  |
|  | О/Н | BS42-V                         | 2K4                        | HC42R                  |

NOTE:

O/H: Approved for Overhead Only
U/G: Approved for Underground Only
O/H or U/G Not specified: Approved for either
Both Right Hand and Left Hand is acceptable

In all cases compression type connections should be avoided. Tunnel type or mechanical connections are preferred. Contact EPL for questions or clarification.

Revised: Nov 17<sup>th</sup>, 2016